

TPC46-16

Industrial Panel PC



PC Specs

CPU:	13th Generation Intel® Core™ i7/i5/i3/U-series Processor SoC	O/S:	Win11 IoT / Win11 Pro / Ubuntu
Bios:	UEFI	USB Interface:	3 x USB 3.2 Gen2 1 x USB Type-C (USB 3.2 Gen 2) (support DP 1.4a display out)
Memory:	DDR5 4800, Dual-Channel SO-DIMM, max. 64GB	Security:	TPM 2.0 (Optional)
Storage:	1 x SATA 6Gb/s	Serial Port:	2 x RS-232/422/485, 9-way D-type
Expansion slots:	1 x M.2 2280 M-Key (PCIe 4.0 [x4] x1) 1 x M.2 2230 E-Key (PCIe 3.0 [x1] + USB2.0) 1 x M.2 3052/3042/2242 B-Key (PCIe 3.0)	Second Display:	HDMI, up to 8Kx4K@60Hz or 4Kx2K@120Hz
Ethernet:	1 x Intel® 2.5 Gigabit LAN 1 x Intel® 1.0 Gigabit LAN	Third Display:	DisplayPort 1.4, up to 7680 x 4320 @60Hz 30bpp (supports DP++)
		Optional Wi-Fi:	Single / Dual-band Wi-Fi, 1 or 2 x Antenna

Display

Screen Diagonal:	46" (1168.4mm) Aspect Ratio 16:9
Resolution:	1920 x 1080 @ 60Hz (Native)*
Pixel Pitch:	0.53025mm x 0.53025mm
Display Area:	1018.08mm (H) x 572.67mm (V)
Viewing Angles:	178° (H) / 178° (V)
Brightness:	700 cd/m ²
Contrast Ratio:	4000:1
Response Time:	6.5ms
Colours:	1073.7M 10 bit (8-bit+FRC)

Touchscreen Options

With Touchscreen: Zytronic Projected Capacitive, 10-Point Multi-Touch

Without Touchscreen Anti-Glare PolyCarb Screen Overlay

Power / Environment

Power Supply: 90-265V AC IEC mains input
24V/48V DC Input, Phoenix connector (Optional)

Power Consumption: TBC

Power Settings: AT: Directly PWR On as power input is ready
ATX: Press Button to PWR On after power input ready

Operating Temperature : 0°C to +50°C

Storage Temperature: -20°C to + 60°C

Physical Attributes

Dimensions / Weight: PM: 44kg | MC: 40kg | Chassis: 38kg [approx.]
(For accurate dimensions please contact Sales@nemacom.co.uk)

Housing Material: Standard: Treated Steel - Black Textured Paint finish
Options: 304/316 Stainless Steel | Bespoke Paint | Custom Sizes | Custom Specifications

IP Sealing: Viewable Side Sealed to IP66

Options and Extras

Applications: Automation | Food Processing | Manufacturing | Pharmaceutical | Process Control | Advertising
Digital Signage | Marine

AV Accessories: Nemacom Ltd are an authorised reseller of high quality Kramer products including, Computer Graphics Video
Distribution Amplifiers, Video Switchers, Routers and Cables

Certifications

Safety & Approvals: UKCA

Installation

Mounting Options: Panelmount | Metal Cased (VESA mount) | Chassis/Open Frame

Warranty & Support

Warranty: 3 years return to Nemacom

Support: Full UK Product Lifetime Support



* A full list of supported video standards is available on request.

** Approx. reading, contact Nemacom Ltd for an accurate figure based on a particular configuration.

Address

Unit 6, Morgans Business Park,
Betty's Lane, Norton Canes, Cannock, Stafford-
shire,
WS11 9UU

Phone

+44 (0)1543 495020

Email

sales@nemacom.co.uk